



Luxurious
Media Glass

95-99%
Visual Transparency

75%
Energy Saving



Support
customization



160° view angle



Now and future
latest facade



HD + Up to 95%
transparency



Support play 3D
videos, Pictures, letter



See through display,
Glass+display+control
boxall in one




Easy for installation,
Male+Female connect,
plug and Play




Easy for operation,
Intelligent control
support APP,
Computer, USB



BUILDING CURTAIN WALL



3D DISPLAY SCREEN



WALL GUARDRAIL

Shenzhen Filmbase Technology Co., Ltd.

Email: info@filmbase.cn **Tel:** +86-755-2850-5346

Address: 31F 3A Building, Smart Park, Baolong street, Longgang district, Shenzhen, China



Product Model				
Products	Luxurious 01	Luxurious 02	Luxurious 03	Luxurious 04
Pitch	P4	P5	P5.98	P7.98
Screen brightness (nits)	0~5000	0~5000	0~5000	0~5000
Visual transparency	≥90%	≥90%	≥95%	≥95%
Pixel pitch	4.16×4.16mm	5×5mm	6.23×6.23mm	8.3×8.3mm
Module	124.8×500m	200×500mm	124.6×499mm	166×498mm
Pixel density	57600	40000	25600	14400
Best view distance	≥4m	≥5m	≥6m	≥8m
Viewing angle	≥160°	≥160°	≥160°	≥160°
Average square power	230W	230W	230W	230W
Maximum square power	650W	650W	650W	650W

Product Model			
Products	Luxurious 01	Luxurious 02	Luxurious 03
Pitch	P10	P16	P20
Screen brightness (nits)	0~5000	0~4000	0~5000
Visual transparency	≥95%	≥98%	≥98%
Pixel pitch	10×10mm	15.6×15.6mm	20×20mm
Module	200×500m	250×500m	200×500m
Pixel density	10000	4096	2500
Best view distance	≥10m	≥15m	≥20m
Viewing angle	≥160°	≥160°	≥160°
Average square power	230W	200W	140W
Maximum square power	650W	520W	390W

Structural




Diagram illustrating the structural layers of the LED glass:

- Glass
- Specially manufactured films
- Display layer
- Specially manufactured films
- Glass

Note: Color and thickness do not represent the actual situation, only for the convenience of illustration.

Technical Parameters	
Pixel specification	1R1G1B
Pixel package	SMD2020
Screen material	Tempered Glass
Grayscale level	65536
Refresh rate	≥3840
Brightness adjustment	32X65536
Operating voltage	+5VDC
Working temperature	-20°C~55°C
Storage temperature	-40°C~80°C
Working humidity	10~90%
Storage humidity	5~95%
Control system	Transmitter cards, asynchronous cards, asynchronous playback boxes, video processors

